

Model: OFM-10
10.4" Industrial Open Frame Panel Monitor



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 10.4" SVGA TFT LED Panel support 800×600 pixels
- Input signal : VGA + DVI
- OSD control keys to optimize the display
- Rugged construction design with Heavy Duty Steel Chassis
- 12 VDC input, with AC 100-240V wide range external AC adapter
- Panel mounting design

Specification	
Product Model	OFM-10
LCD Panel	Display Type : 10.4" SVGA TFT (BOE LED Panel) Resolution : 800×600 Max. color : 16.2M Brightness : 400 cd/m2 View Angel : 140°(H) , 160°(V) Contrast Ratio : 700 : 1 MTBF : 50,000hrs
Signal Input	VGA (15 pin D-sub connector) + DVI (DVI-D)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and Source
Signal Connectivity (optional)	Support AV input (VGA + BNC)
Power Supply	Input: 100~240VAC,50/60Hz Output: DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel chassis
Environment	Operating temperature: 0°C to 50°C Storage temperature: -10°C to 60°C Storage humidity: 10% to 95%, non-condensing Vibration: 5 to 500HZ 1G PTP

	Shock: 15G peak (11m second)
Compliance	CE/FCC/Rohs
Dimension W x H x D (mm)	261 x 223 x 32

Ordering Information

OFM-10	10.4" Industrial Open Frame Panel Monitor
Optional: AV	Support AV Input (VGA + BNC)

Structure Diagram Unit: mm

